




Remark: Minimum speed 30RPM

Matchservo Motor & Drives



SHUNYANG ELECTRICAL MACHINERY MANUFACTURE CO., LTD

廣州市順揚機電有限公司

(台灣愛德利科技股份有限公司中國授權商標使用及專業製造商)

廣東：廣東省廣州市增城區新塘鎮白江村田厝靶嶺 3 路 8 號首層

NO.8 XIAPAILING ROAD, XINTANG TOWN, ZHENCHENG BROUGH, GUANGZHOU CITY, GUANGDONG PROVICE, CHINA.

电话 (TEL) : +86-20-32371818 传真 (FAX) : +86-20-32371828 E-MAIL : ADLII@QQ.COM



Innovated Matchservo Motor

- Low noise, Minimize EMI and maintenance free.
- Specialized designation to have smoother shaft rotation and improved reliability.
- Light weight and compact size, higher power density, torque density and efficiency than conventional motors.
- A wide range of high-efficiency operation speed 30 RPM ~ 3000RPM, suitable for the load changes, speed variation operating conditions are generally advantages that conventional motors can't achieve.




Intelligent Drive Controller

- The drive provides position, speed and torque for three kinds of basic modes operation.
- Digital I / O output into regulation.
- Dual system control by torque and speed.
- Internal drive provides 8 segments speed, two-stage acceleration and deceleration control.
- Internal drive 7 segment provides position location, a return HOME mode, eliminate the cumulative amount of error, precise, no need of PC (such as HMI, PLC) control, save costs on PC, and therefore more in line with market demand.
- Available for all control interfaces, ex. RS 485, direct signal, PLC and HMI.
- Drive provides 24VDC for SENSOR require.
- Speed rendering and real output DC10V for external control header.
- Drive signals can be output 128 PPR for external control using.
- Position tolerance on high speed, avoid over-current, over-voltage and motor blocked protection against abnormal occurs.




Driver Dimensions



• SD2-101M/H~SD2-107M/H 1



• SD2-115M/H~SD2-122M/H 2 • SD4-307M/H~SD4-322M/H



• SD2-337M~SD2-375M 3 • SD4-337M~SD4-375M



MA4 Servomotor Specification

Rated Power	W	750W	1.5KW	2.2KW	3.7KW	5.5KW	7.5KW
Servomotor Model No.		MA4-750M/H	MA4-1500M/H	MA4-2200M/H	MA4-3700M	MA4-5500M	MA4-7500M
Rated Torque	N.m	M:2.39/H:1.2	M:4.78/H:2.39	M:7.17/H:3.59	11.78	17.5	23.8
Max. Torque	N.m	M:7.18/H:3.6	M:14/H:7.17	M:20.3/H:10.77	29.4	43.75	59.5
Rated Current	Arms	M:2.0/H:1.9	M:4.4/H:3.8	M:6.9/H:6.3	10	14.7	19.5
Max. Current	Arms	M:6.0/H:6	M:13.2/H:11	M:20.7/H:18	25	36.75	48.75
Rated Speed	RPM	M:3000/H:6000					
Torque Constant-KT	N.m/Arms	M:1.27/H:0.74	M:1.18/H:0.77	M:1.16/H:0.76	1.29	1.36	1.36
Rotor Moment of Inertia	10 ⁻⁴ *kgm ²	M:2.59/H:2.26	M:12.8/H:11.5	M:18.2/H:14.5	63.3	93.5	115
Mechanical Time Constant	ms	M:1.99/H:2.21	M:1.60/H:2.86	M:1.35/H:2.06	4.08	3.20	1.81
Electric Time Constant	ms	M:2.84/H:5.6	M:7.91/H:10.75	M:7.95/H:13.76	19.96	27.61	29.71
Insulation		Class F					
IP Rating		IP65 (When an Oil Seal is Used to be Fitted to the Rotating Shaft)					
MA4 Dimension Figure No.		FIG D	FIG E	FIG F	FIG G	FIG H	FIG I
MA4 Motor Weight	Kg	M:4.7/H:4.7	M:10/H:9	M:12/H:10.5	20	25.5	29



SD4 Servo Driver Specification

Rated Power	W	750W	1.5W	2.2KW	3.7KW	5.5KW	7.5KW
Drive model No.		SD4-307M/H	SD4-315M/H	SD4-322M/H	SD4-337M	SD4-355M	SD4-375M
Motor model No.		MA4-750M/H	MA4-1500M/H	MA4-2200M/H	MA4-3700M	MA4-5500M	MA4-7500M
Input Voltage	AC	380V±10% 3ø					
Input Frequency	Hz	50 / 60					
Rated Output Current	Arms	M:2.0/H:1.9	M:4.4/H:3.8	M:6.9/H:6.3	10	14.7	19.5
Max. Output Current	Arms	M:6.0/H:6	M:13.2/H:11	M:20.7/H:18	25	36.75	48.75
Encoder Type and Resolution		A、B、Z、HU、HV、HW Open Collector. (A、B Phase= 128PPR)					
ACC. DEC. Time		0.1~60.0 Sec.					
Speed Regulation	Load	±0.3%Below (0~Rated Torque at Rated Speed)					
	Voltage	±0.3%Below (Source Voltage ± 10%at Rated Speed no Load)					
	Temperature	±0.3%Below (0~45°C / 32~113°F at Rated Speed no Load)					
Type of Control		Sin PWM					
Model of Control		1. Speed mode 2. Torque mode 3. Position mode					
Input Signal	Analog Panel	1. Vref, Tref ± 10V Analog Input 2. Panel VR 0~5V Analog Input					
	Digital Panel	DI0 ~ DI6 and COM common, Input Impedance 4.7KΩ to common					
Output Signal		DOx Open Collector (x=0~3), External Voltage(48VDC, 50mA below). Magnet brake relay please set at DO3.					
Protection		Overload, Over Current, Over Voltage, Over Heat Encoder Abnormal, Short Circuit					
SD4 Dimension	Fig	FIG 2	FIG 2	FIG 2	FIG 3	FIG 3	FIG 3
SD4 Weight	Kg	1.1	1.3	1.3	5	6	6



Motor Dimensions

- MA2-120M/H~MA2-750M/H
- MA4-750M/H




FIG. NO.	CP	PM	PS	PH	T	L	LA	LB	LD	LE	AE	AD	SHAFT END					
FIG. A													ED	Q	E	AD	GA	F
FIG. B	90	104	6.5	83	2.5	175	8	143	57.5	66.5	66.6	77.6	25	29	32	14	16	5
FIG. C						190		156	72.5									
FIG. D						245		213	127.5									

UNIT:mm

- MA2-1500M/H~MA2-2200M/H
- MA4-1500M/H~MA4-2200M/H




FIG. NO.	CP	PM	PS	PH	T	L	LA	LB	LD	LE	AE	AD	SHAFT END					
FIG. E	130	145	9	110	3.5	261.5	12	211.5	123.5	69	68.6	113.3	45	50	50	24	27	8
FIG. F						288.5		238.5	150.5									

UNIT:mm

- MA2-3700M~MA2-7500M
- MA4-3700M~MA4-7500M




FIG. NO.	CP	PM	PS	PH	T	L	LA	LB	LC	LD	LE	AB	AC	AD	AE	KK	SHAFT END							
																	ED	Q	E	AD	GA	F	OH	
FIG. G						359.5		280.5	261.5	167								63	73	79	35	38	10	M12
FIG. H	180	200	13.5	114.3	4	454.5	18	341.5	322.5	166	111	111	116.5	147	66.6	33.5		90	106.5	113	42	45	12	M16
FIG. I						484.5		371.5	352.5	196														

UNIT:mm

MA2 / SD2

MA2 Servomotor Specification

Rated Power	W	120W	180W	370W	750W	1.5KW	2.2KW	3.7KW	5.5KW	7.5KW
Servomotor Model No.		MA2-120M/H	MA2-180M/H	MA2-370M/H	MA2-750M/H	MA2-1500M/H	MA2-2200M/H	MA2-3700M	MA2-5500M	MA2-7500M
Rated Torque	N.m	M:0.38/H:0.19	M:0.57/H:0.29	M:1.18/H:0.59	M:2.39/H:1.2	M:4.78/H:2.39	M:7.17/H:3.59	11.78	17.5	23.8
Max. Torque	N.m	M:1.16/H:0.57	M:1.73/H:0.87	M:3.53/H:1.77	M:7.18/H:3.6	M:14.0/H:7.17	M:20.3/H:10.76	29.4	43.75	59.5
Rated Current	Arms	M:0.65/H:0.6	M:0.9/H:0.8	M:1.95/H:1.6	M:3.5/H:3.0	M:7.6/H:6.5	M:12/H:10	18	24.5	32.0
Max. Current	Arms	M:1.17/H:1.8	M:2.5/H:2.4	M:5.88/H:4.8	M:10.2/H:9	M:22.8/H:18.5	M:36/H:30	45	61.3	80
Rated Speed	RPM	M:3000/H:6000								
Torque Constant-KT	N.m/Arms	M:0.71/H:0.44	M:0.71/H:0.44	M:0.7/H:0.45	M:0.71/H:0.45	M:0.67/H:0.44	M:0.64/H:0.44	0.72	0.78	0.76
Rotor Moment of Inertia	10 ⁻⁴ kgm ²	M:1.11/H:1.12	M:1.11/H:1.12	M:1.57/H:1.42	M:2.59/H:2.26	M:12.8/H:11.5	M:18.2/H:14.5	63.3	93.5	115
Mechanical Time Constant	ms	M:3.69/H:4.32	M:3.69/H:4.32	M:2.54/H:2.74	M:1.75/H:2.59	M:1.64/H:2.84	M:1.43/H:2.91	4.47	2.58	2.23
Electric Time Constant	ms	M:2.15/H:3.54	M:2.15/H:3.54	M:2.51/H:4.25	M:3.35/H:4.9	M:7.77/H:10.73	M:8.74/H:10	19.7	24.8	25.3
Insulation		Class F								
IP Rating		IP65 (When an Oil Seal is Used to be Fitted to the Rotating Shaft)								
MA2 Dimension		FIG A	FIG B	FIG C	FIG D	FIG E	FIG F	FIG G	FIG H	FIG I
MA2 Weight	Kg	M:2.4/H:2.4	M:2.4/H:2.4	M:3.9/H:3.1	M:4.7/H:4.3	M:10/H:9.1	M:12/H:10.5	20	25.5	29

SD2 Servo Driver Specification

Rated Power.	W	120W	180W	370W	750W	1.5KW	2.2KW	3.7KW	5.5KW	7.5KW
Drive model No.		SD2-101M/H	SD2-102M/H	SD2-104M/H	SD2-107M/H	SD2-115M/H	SD2-122M/H	SD2-337M	SD2-355M	SD2-375M
Motor model No.		MA2-120M/H	MA2-180M/H	MA2-370M/H	MA2-750M/H	MA2-1500M/H	MA2-2200M/H	MA2-3700M	MA2-5500M	MA2-7500M
Input Voltage	A	220V±10% 1Ø						220V±10% 3Ø		
Input Frequency	H	50 / 60								
Rated Output Current	Arms	M:0.65/H:0.6	M:0.9/H:0.8	M:1.95/H:1.6	M:3.5/H:3.0	M:7.6/H:6.5	M:12/H:10	18	24.6	32.0
Max. Output Current	Arms	M:1.7/H:1.8	M:2.5/H:2.4	M:5.88/H:4.8	M:10.2/H:9.0	M:22.8/H:18.5	M:36/H:30	45	61.3	80
Encoder Type and Resolution		A · B · Z · HU · HV · HW Open Collector. (A · B Phase= 128PPR)								
ACC. DEC. Time		0.1~60.0 Sec.								
Speed	Load	±0.3%Below (0~Rated Torque at Rated Speed)								
Regulation	Voltage	±0.3%Below (Source Voltage ± 10%at Rated Speed no Load)								
	Temperature	±0.3%(Below (0~45℃ / 32~113℉ at Rated Speed no Load)								
Type of Control		Sin PWM								
Model of Control		1. Speed mode 2. Torque mode 3. Position mode								
Input Signal	Analog Panel	1. Vref, Tref ± 10V Analog Input 2. Panel VR 0~5V Analog Input								
	Digital Panel	DI0 ~ DI6 and COM common, Input Impedance 4.7KΩ to common								
Output Signal		DOx Open Collector (x=0~3), External Voltage(48VDC, 50mA below). Magnet brake relay please set at DO3.								
Protection		Overload, Over Current, Over Voltage, Over Heat Encoder Abnormal, Short Circuit								
SD2 Dimension	Fig	FIG 1	FIG 1	FIG 1	FIG 1	FIG 2	FIG 2	FIG 3	FIG 3	FIG 3
SD2 Weight	Kg	1.1	1.1	1.1	1.1	1.3	1.3	5	6	6